reelink	Nink Reolink Innovation Limited	
Picture		
Model		Argus Series B330
	Image Sensor	1/2.7"CMOS sensor
Video & Audio	Resolution	2880 x 1616 (5 megapixels) @15fps
	Video Compression	H.265
	Field of View	Horizontal: 105°
		Vertical: 55°
		Diagonal: 125°
	Infrared Night Vision	Up to 10 meters (33ft); LED: 6pcs/0.8w/850nm
	Color Night Vision	With spotlights: 2pcs/2w/6500k
	Frame Rate	Main stream: 10fps - 15fps (default: 15fps)
		Sub stream: 10fps - 15fps (default: 15fps)
	Code Rate	Main stream: 1024Kbps - 4096Kbps (default: 3072Kbps)
		Sub stream: 64Kbps - 672Kbps (default: 672Kbps)
Power Requirements	Battery	Two-way audio 6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)
Interface	Power Port	USB Type-C port
	SD Card Slot	Supports Max. 128GB microSD card
	Reset Button	YES
	Audio In/Out	Built-in microphone and speaker
Wi-Fi	Wireless Standard	IEEE 802.11 a/b/g/n
	Operating Frequency	2.4GHz/5GHz
	Wireless Security	WPA/WPA2
Software	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
	User Access	Max. 12 simultaneous streams (2 main & 10 sub streams)
Other Features	Smart Alarm	PIR detection; person detection; vehicle detection; pet detection
	PIR Detecting Distance	Adjustable up to 10m (33ft)
	PIR Detecting Angle	100° horizontal
	Recording Modes	Triggered recording
	Time Lapse	YES
	Smart Home Compatibility	Google Assistant; Alxea
	Cloud Storage	Supports Reolink Cloud (available in selected countries)
Working Environment	Operating Temperature	-10°C~+55°C (14°F~131°F)
	Operating Humidity	20% ~ 85%
	Weatherproof	IP65
Mechanical	Dimensions	127 x 90 x 56mm
	Weight (Battery Included)	330g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.